




Conectore estanco recto macho con rosca CRMF



- **APLICACIONES**
Utilizados para la unión entre el caño flexible con extremo roscado.
- **CARACTERISTICAS CONSTRUCTIVAS**

MATERIALES:
 - Aluminio.
ROSCAS:
 - Se proveen con roscas desde 1" hasta 4" NPT o BSP.

P/Flexible	Rosca NPT ó BSP-T	Dimensiones en mm		
		A	B	C
3/8"	1/2"	35	23	13
1/2"	1/2"	35	23	13
3/4"	3/4"	42	27	15
1"	1"	48	30	18
1 ¼"	1 ¼"	60	36	21
1 ½"	1 ½"	69	36	21
2"	2"	82	39	20
2 ½"	2 ½"	106	57	27
3"	3"	121	63	28
4"	4"	147	71	35

- **CODIFICACION**
CRMF-065

Indica **Tipo de rosca** - 5 = BSP
- 7 = NPT

Indica **Diámetro de rosca** - 1 = 1/2"
- 2 = 3/4"
- 3 = 1"
- 4 = 1 1/4"
- 5 = 1 1/2"
- 6 = 2"
- 7 = 2 1/2"
- 8 = 3"
- 9 = 4"

Indica **Línea** - CRMF = Conector recto macho con rosca